



REDDYFUELS cc. CK 2009/213665/23
 Postal Address: 57 Clifton Avenue, Lyttelton, Centurion, 0157
 Telephone: +27 12 664 1969
 Mobile Contacts: +27 83 236 7702 / +27 83 634 1339
 Fax: +27 (0) 12 664 1969 or +27 (0) 86 538 7313

HFO 150

	UNIT	TYPICAL	SPECIFICATION	METHOD
Gross Energy Content (CV)	kJ/kg	43 400	41 900 min	ASTM D240
Viscosity @ 50°C	cst	140	150 max	ASTM D445
Total Sulphur	Mass %	3,2	3,5 max	ASTM D129 IP 242
Pour Point	°C	-10	0 max	ASTM D97
Flash Point	°C	95	61 max	ASTM D93
Water Content	Mass %	0,45	0,75 max	ASTM D95
Density @ 20°C	Kg/litre	0,98	Report	ASTM D1298
Ash	Mass %	0,05	0,1 max	ASTM D482

ADDITIONAL PRODUCT INFORMATION

COLOUR	BROWN/BLACK
CLARITY	BRIGHT
COMPOSITION	HYDRO-CARBON RESIDUAL AND DISTILLATE BLEND
SAFETY	REFER MSDS HFO

*This product complies with CKS 142-1989 as published by the SABS